



SEWING MACHINES



39800CA

39800CB 39800CP

39800CQ

39800CX

39800CY

39800VCP

39800VCX

39800VCY

CATALOG


No.

Third Edition




SMALL FRAME HIGH SPEED FOUR AND FIVE THREAD SAFETY STITCH VERTICAL NEEDLE MACHINES

UNION SPECIAL CORPORATION




MAIN FRAME, MISCELLANEOUS COVERS, PLATES AND BUSHINGS

Ref.	Part		Ant.
No.	No.	Description	Req.
1	22894 AG	Screw, for top cover	= 2
2	39882 G	Top Cover	- 1
3	39882 E	Upper Oil Shield Cover	1
4	22541 B	Screw, for upper oil shield cover	- 12
5	39882 F	Gasket, For upper oil shield cover	- 1
6	39893 C	Screw, for oil system	= 4
8	39852 M	Needle Lever Drive Shaft Bushing	
9	22569	Screw, for cloth plate stud	= 1
10	39501 K	Clorb Place Stud	- 1
11	8372 A	Washer, for oil filter screen screw	= 1
12	22824 B	Screw, for oil filter screen	- 1
13	39855 D	Foot Lifter Shaft Bushing	- 2
14	39573 K 39573 AA	Upper Knife Uriving Arm Bushing, loft	E 4
16	39544 L	Lower Locper Bar Bushing	
17	39644 C	401 Looper Drive Shaft Bushing, right	- 1
18	39644 S	401 Looper Drive Shaft Bushing, left	
19	39590 T	Crankshaft Bushing, Inner left	- 1
20	39590	Crankshaft Bushing, left	- 1
21	39834 8	Differential Feed Bar Thrust Wosher	- 1
23	22569 G 39894 B	Screw, for feed bar thrust washer	- 1
24	39894 A	Oil Filter Screen	- 1
25	39578 F	Cloth Plate Fabric Guard	- 1
26	138	Screw, for cloth plate fabric guard	- 2
27	22657 D-12	Screw, for cloth plate	- 1
28	39501 DN	Cloth Place, for Styles 39800 CA, CB, CF, CQ, CK, CY	- 1
	39501 DU	Cloth Plate, for Styles 39800 VCP, VCQ, VCX, VCY (not shown)	- 1
29 30	39832 90	Cloth Plate Latch Spring	- 1
31	666-268	Felt Pad	- 4
32	39593 K	Oil Tube, typothana	- 1
33	666-271	Oil Tobe, brass	- 1
94	660-506	Retaining Ring, for oil tube	- 1
35	56393 G	Porex Filter, for oil tube	- 1
36	56393 V	Spring, for oil tube	- 1
37 36	51295 B 39882	Isolator	7 7
39	22806 A	Screw, for bottom cover	- 1
40	39882 J	Bottom Cover Gasket	- 1
4.1	22541 B	Screw, for bottom cover	- 13
42	39593 C	Oil Caugu Float	- 1
4.3	22586 R	Screw, for bottom cover	= 1
44	39595	Isolator	- 2
45	22569 D 39582 BL	Screw, for lower and outer air duct	= #
47	39382 HK	Air Duct, lower	
48	22541 B	Screw, for base plate	- 2
49	39582 BM	Rose Plate	- 1
50	22569 C	Screw, for upper air duct	- 2
51	8372 A	Washer, for upper mir duct screw	- 2
52	39382 BV	Air Duct, upper	- 1
53	22653 D-4 39382 F	Screw, for base plate extension	- 1
55	39382 E 39593 J	OII Puno Tube	- 1
56	22369 0	Screw. for oil tube spring	= 1
57	39393 D	Oll Cance Indicator	- 1
58.	39591 L	Spring, for oil tube	- 1
59	666-280	Oil Tibe, tygothane	= 11
60	22650 AE-4	Plug Screw	- 1
61	666-290	Pelt Disc erectedence contract	- 1




CRANKSHAFT AND FEED MECHANISM

Ref.	Part		And.
No.	No.	Description	Reg.
1:	39690 A 39890 C	Stud, for crankshaft bearing	
3	660-443	"O" Ring, for crankshaft bearing, inner right	
4	39591 H	Crank Chamber Cooling Fan Collar	- 1
5	22894 D	Spot Screw, for crank chamber cooling fan coliar	- 2
6	39591 L	Crank Chamber Cooling Fan	= 1
7 8	39590 .	Thrust Washer	
9	39590 G 550-268	Grankshaft Ball Bearing Housing	
10	39590 E	Ball Bearing Stop Collar	
11	39590 S	Spacer Collar	- 1
12	22569 В	Screw, for ball bearing retaining plate and housing	- 3
13	39521 G	Pulley	- 1
1.4	- 95	Screw, for pulley	- 2
15	22769 B	Screw, for pulley cap	- 1
17	39821 39590 H	Pulley Cap	
18	29477 MF	Grankshaft Ball Bearing Retaining Plate Grankshaft and Needle Driving Connecting Rod Assembly, for Styles	- 1
20	SALVONE	39800 CA and CB	G 1
100	29477 MB	Grankshaft and Needle Driving Connecting Rod Assembly, for all	
		Styles except 39800 CA and CB	- 1
19	3985Z A	Needle Driving Connecting Rod Assembly	- 1
20	. 27.	Screw	- 1
21	22587 M 39516-625		
44	39516-626	Needle Bearing, .0625 inch (1.588 mm) diameter Reedle Bearing, .0626 inch (1.590 mm) diameter	- 28
_	39516-627	Needle Searing, .0627 inch (1.590 mm) diameter	- 28
23	30-106 B11	k. Wood Plug, birch	- 20
24	51-228 B1		- 1
25	39541 A	Feed Driving Eccentric Key	- 1
2.6	C067 E	Cork Plug	
27	258	Nut	
28 29	39890 E 97 A	Split Bearing and Oil Pump	
30	39691	Screw, for split bearing and oil pump	5 5
31	39593 J	Oil Pump Tube	- 4
32	22747 B	Screw, for crankshaft counterweight	- 4
33	39591 K	Grankshaft Counterweight, left	- 1
34	39835 B	Fred Adjusting Pin	- 1
35	22896 1	Screw, for feed adjusting pin and feed bar guide, right	
36 37	39835 C 22894 U	Feed Leveling Lever	
35	39535 J	Feed Bar Guide Block	- 1
39	39835 A	Feed Bar Guide, right	
40	39536 B	Feed Bur Driving Stud	- 2
41	39534 G	Differential Feed Bar	- 1
42	39534	Main Feed Bar	
43	39536 C	Feed Bar Driving Stud Bushing	
45	39536 E 39536 AF	Not, for feed bar driving stud	
46	39536 AF 39868 B	401 Looper Thread Take-up	E +
47	39540 E-10	Main Feed Driving Eccentric, for No. 5 1/8 gauge, all Styles	- 1
-	39540 E-8	Main Food Driving Eccentric, for No. 8 3/16 or 12 3/16 gauge,	- '
		nll Styles	- 1
48	39540 B-10	Differential Feed Driving Eccentric, for No. 5 1/8 gauge,	
	20510-0-0	all Styles	
-	39540 E-8	Differential Feed Driving Eccentric, for No. 8 3/16 or 12 3/16 gauge all Styles	
40	39536 AE	Differential Feed Bar Driving Connection	- 1
50	93 A	Screw, for main feed dog	2 1
51		Main Feed Dog (See Pages 43 and 45)	- 1
52	39838	Feed Lift Block	- 1
53	93	Screw, for differential feed dog	- 1
54		Differential Feed Dog (See Pages 43 and 45)	- 1




NEEDLE DRIVE MECHANISM AND TAKE-UPS

Ref.	Part	Amt.
No.	No.	
1	39852 J	Needle Guide Bar 1
2	22733	
-	CL21	Screw, for needle guide bar 1 Pipe Cleaner (oil wick) 1
3 4	22894 C	Set Screw
5	22894 L	Spot Screw 1
6	39852 C	Needle Lever Roller Pin1
7	W0-3	Wool Yarn as required
8	660-220	"O" Ring, for needle guide bar 1
9	660-416	Retaining Ring, for needle lever roller pin 2
-10	39852	Needle Lever 1
11	22852 C	Screw, for needle lever
12	40-139	Washer, for needle lever1
13	39863 C	Lower Looper Thread Take-up Wire 2
14	39852 E	Needle Lever Drive Shaft 1
15	39573 A	Thrust Washer
16	660-442	Retaining Ring, for needle lever drive shaft 1
17	39852 D	Needle Drive Lever 1
18	22852 C	Screw, for needle drive lever 1
19	40-139	Washer, for needle drive lever 1
20	51236 A	Link Pin, for needle drive lever 1
21	W0-3	Wool Yarm as required
22	39843 D	Needle Lever Drive Shaft Thrust Clamp Collar 1
23	22652 B-10	Screw, for thrust clamp collar 1
24	22588 A	Screw, for needle thread cam pull-off 1
25	39863 D	503 Needle Thread Cam Pull-off
26	39863 J	401 Needle Thread Cam Pull-off!
27	39863	Lower Looper Thread Take-up Lever 1
28	22752 B	Screw, for take-up lever
29	22564 D	Screw, for take-up lever wire 4
30	39852 F-5	Needle Head, marked "AV", for No. 5 1/8 gauge, all
	2243474747	Styles
-	39852 F-8	Needle Head, marked "BN", for No. 8 3/16 gauge, all
	50000 m 10	Styles1
-	39852 F-12	Needle Head, marked "AW", for No. 12 3/16 gauge, all
31	22784 L	Styles1
32	39852 N	Screw, for top needle head eyelet 1
33	28 C	Needle Head Eyelet, top 1 Screw, for needles 2
34	39852 K-5	
2.9	39852 K-8	Needle Head Eyelet, for No. 39852 F-5 1 Needle Head Eyelet, for No. 39852 F-8 1
- 8	39852 K-12	Needle Head Eyelet, for No. 39852 F-121
3.5	22738 B	Screw for 39852 F-5 or 39852 F-8
20	605	Screw, for No. 39852 P-12
36	120 GS	Needle, for all 5 1/8, 8 3/16 gauge machines; 12 3/16
	120 00	gauge on Styles 39800 CA and CB 2
-	120 GAS	Needle, for all 12 3/16 gauge machines except Styles
		39800 CA and CB 2
37	39594 N	011 Splasher
38	87 U	Screw, for oil splasher
		TOTAL TOTAL CONTROL OF THE PARTY OF THE PART




LOWER LOOPER DRIVING MECHANISM

Ref.	Part	Amt.
No.	No.	Description Req.
1	39808 D	Lower Looper, marked "ACZ" 1
2	39151	Nut, for lower looper bar1
3	52344	Lower Looper Bar 1
4	77	Screw, for connecting link pin 1
5	660-206	"O" Ring, for lower looper bar driving lever shaft 1
6	22894 AE	Screw, for lower looper bar driving lever shaft 2
7	482 C	Lower Looper Shaft Collar1
8	22894 C	Screw, for collar 2
9	39894 C	Oil Pump Oiler 1
10	12982	Nut, for oil pump oiler screw1
11	22894 J	Screw, for oil pump oiler1
12	538	Screw, for ball joint guide fork 2
13	39644 X	Ball Joint Guide Fork1
14	39644 R-2	Shim, for ball joint guide fork, .002 inch (.051 mm)
		thick as required
-	39644 R-5	Shim, for ball joint guide fork, .005 inch (.127 mm)
		thick as required
15	666-255	Felt Plug, for lower looper drive lever connecting rod 1
16	39644 F	Lower Looper Drive Lever Connecting Rod 1
17	22729 D	Screw, for connecting rod 2
18	22729 E	Screw, for connecting rod 2
19	77	Screw, for connecting link pin 1
20	39844	Lower Looper Bar Driving Lever 1
21	39844 B	Lower Looper Bar Driving Lever Shaft 1
22	39544 D	Lower Looper Bar Connecting Link Pin 2
23	39544 B	Lower Looper Bar Connecting Link 1




Ref.	Part		Amt.
No.	No.	Description	Req.
1	9937	Nut, for upper knife clamp stud	1
2	39871	Upper Knife Clamp	1
3	39870	Upper Knife	1
4		Upper Knite	1
	22738	Screw, for upper knife clamp stud	1
5	39572 A	Upper Knife Holder Block	1
6	39571 C	Upper Knife Clamp Stud	1
7	39873 B	Upper Knife Driving Arm Thrust Washer	1
8	39873	Upper Knife Driving Arm	1
9	39573 A	Upper Knife Driving Arm Thrust Washer	1
10	39573 E	Upper Knife Driving Lever	1
11	55235 D	Locking Stud, for driving lever	
12	6042 A	Washer, for driving lever	1
13	55235 E	Nut, for driving lever	1
14	39673	Upper Knife Driving Lever Connecting Rod	1
15	22587 E	Screw, for connecting rod	2
16	22565 C	Set Screw, for bushing and cam guide	
17	39644 K	Bushing and Cam Guide, for Styles 39800 CA and CB	
-	39644 V	Bushing and Cam Guide, for all Styles except 39800 CA and CB	
18 19	22729 M	Screw, for bushing and cam guide	
20	39644 P 98	Thrust Collar	
20	482 C	Screw, for thrust collar	2
22	22894 C	Looper Drive Lever Shart Collar	1
23		Screw, for collar	2
24	39644 39543 P	Looper Bar Thrust Washer	
25	39543 M		2
26	22562 A	Screw, for clamp collar	
27	39644 U	Looper Drive Lever Auxiliary Connecting Rod	
28	22729 E	Screw, for connecting rod	
29	22729 D	Screw, for connecting rod	
30	39644 R-2	Shim, for ball joint guide fork, .002 inch (.051 mm)	
30	37044 11-2		required
-	39644 R-5	Shim, for ball joint guide fork, .005 inch (.127 mm)	
- 3			required
31	39644 X	Ball Joint Guide Fork	
32	538	Screw, for ball joint guide fork	
33	660-206	"0" Ring, for looper drive lever shaft	
34 35	22894 AE	Screw, for looper drive lever shaft	2
36	39644 N 39644 A	Looper Bar (401 stitch)	1
37	39844 A	Looper Holder, for 401 stitch looper	
38	22652 A-6	Screw, for looper holder	
39	22894 AF	Screw, for looper	1
40	39808	Looper, marked "CY", for 401 stitch	
41	22503 F	Screw, for cam follower locking clamp	
42	39543 E	Cam Follower Locking Clamp	- 1
43	39644 W	Looper Bar Sleeve	1
44	39644 L	Cam Follower	
45	39571 B	Upper Knife Chain Guard	
46	39536 E	Nut, for looper avoid eccentric stud	
47	22781	Screw, for looper avoid link pin	1
48	41336 C	Looper Avoid Link Pin	1
49	39844 C	Looper Avoid Link	1
50	39844 D	Looper Avoid Eccentric Stud	
*51	22775	Screw, for looper avoid link	
*52	39644 M	Looper Avoid Link	1

^{*} Used on earlier model machines, in place of Ref. Nos. 46, 49 and 50.



		PLAIDS AND DOWLK BRIFE PARTS
Ref.	Part	Ant.
No.	No.	Description Req.
1	39808 A	Upper Looper, marked "DA", for 100/040 needle size and smaller, for Styles
	39808 C	39800 CB, CQ, CY, VCQ, and VCY; all gauges 1
-	39808 C	Upper Looper, marked "ADA", for 110/044 needle size and larger, for Styles
1A	39860	39800 CB, CQ, CY, VCQ and VCY; all gauges1
2	39543	Upper Spreader, marked "H", for Styles 39800 CA, CP, CX, VCP and VCX; all gauges 1 Upper Looper or Spreader Holder, marked "J" 1
2A	22564 G	Screw, for upper looper or spreader 1
** 3	39543 H	Upper Looper or Spreader Holder 1
3A	22768 B	Screw, for upper looper or spreader1
4	39543 H	Upper Looper or Spreader Holder Collar
5	22 KH	Screw, for upper looper or spreader holder collar1
6	22565 R	Screw, for bushing and can guide1 Lock Screw, for bushing and can guide screw1
7	1025 L	Lock Screw, for bushing and can guide screw 1
* 9	39543 T	Cam Follower1
*10	39543 S	Upper Looper or Spreader Drive Shaft Bushing and Cam Guide 1
11	39843 A 22503 F	Upper Looper or Spreader Drive Shaft
12	39543 E	Cam Follower Locking Clamp
13	666-255	Folt Flug, for upper looper or spreader drive lever connecting rod1
14	97	Screw for builds fork
1.5	39544 J	Screw, for guide fork 2 Guide Fork 1
16	W0-3	Wool Varn for head
17	12982	Nut 1
18	22894 J	Screw
19	482 C	Upper Looper or Spreader Drive Lever Shaft Collar 1
20	22894 C	Screw, for collar2
21	660-206	"O" Ring, for upper looper or spreader drive lever shaft 2
22	22894 C 39843 C	Set Screw, for upper looper or spreader drive lever shaft 1
24	22894 L	Upper Looper or Spreader Drive Lever Shaft 1
25	39543 M	Spot Screw, for upper looper or spreader drive lever shaft1
26	22562 A	Screw, for clamp collar
27	39543 P	Thrust Washer, for upper looper or spreader drive shaft, for Styles 39800 CA and CB 2
-	39843 E	Thrust Washer, for upper looper or spreader drive shaft, for all Styles except
		39800 CA and CB
28	39843 B	Upper Looper or Spreader Drive Lever Thrust Washer 1
29	39543 W	Upper Looper or Spreader Drive Lever
30	39843	Upper Looper or Spreader Drive Lever Connecting Rod 1
31 32	22729 D 87 U	Screw, for connecting rod 4 Screw, for oil splasher 1 011 Splasher
33	39594 N	Screw, for oil splasher1
34	22524	Screw, for throat plate 1
35	20704	Throat Plate, (See Pages 43 and 45)
36	39650 A	Lower Knife Clamp Screw Nut
37	39550 E	Knife Holder Spring
38	39625 D	Needle Guard, front, for 401 stitch needle
39	39825 C	Needle Guard, rear, for 401 stitch needle
40	39825 B	Needle Guard, rear, for 503 or 504 stitch needle1
41	22585 A	Screw, for 503 or 504 stitch needle guard 2
42	90	Screw, for 401 stitch front needle guard 1
43	39825 7 39880	Needle Guard, front, for 503 or 504 stitch needle 1
45	39880 H	Throat Plate and Lower Knife Support Bracket1 Shim, for throat plate support barcket as required
46	39580 F	
47	22653 B-12	Washer, for support bracket screw 2 Screw, for support bracket 2
48	39543 E	Needle Guard Locking Clamp1
49	88 F	Screw, for needle guard locking clemp 1
50	22892 3	Locking Screw, for lower knife holder
51	14077	Nut, for locking screw
52	39550 C	Lower Knife Holder Locating Stud1
53	22729 3	Screw, for lower knife holder locating stud1
54	39650	Lower Knife Holder 1
55 56	39849 39550 M	Lower Knife 1
56 57	39550 M 39550 Z	Lower Knife Clamp Spring
58	22588 J	Screw, for lower knife clamp
59	39883	Screw, for stabilizing 401 stitch front needle guard
60	41071 G	Nut, locking
		1

^{*} Replacement with assembly No. 29126 EX is recommended, instead of the individual parts.
** Upper Looper or Spreader Holder No. 39843 H is used on later model machines.



THREAD TENSIONS, EYELETS AND PRESSER SPRING PARTS Description

Ant.

Req.


Ref. Part No. No.

1	22569 B	Screw, for eyelet and fabric guard mounting bracket 1
2	53634 C	Washer, for mounting bracket screy
3	39868 D	Upper Looper Thread Eyelet and Fabric Guard Mounting Bracket
4	39568 L	opper booper intend byeter and rabite odare mounting fracket
-4	39300 L	Upper Looper Take-up Eyelet, on Styles 39800 CB, CQ, CY, VCQ and VCY;
		all gauges 1
5	39568 E	Auxiliary Upper Looper Thread Eyelet, on Styles 39800 CB, CQ, CY, VCQ and VCY;
		all gauges
6	39868 X	Lower Looper Cast-off Blade
7	376 A	Screw, for upper looper take-up eyelet on Styles 39800 CB, CQ, CY, VCQ and VCY;
		all gauges
8	39868 Y	Fabric Guard
9	376 A	Screw, for fabric guard
10		Screw, for fabric guard 1
	39557 B	Presser Spring Plunger Cap Nut1
11	39857 L	Presser Spring Plunger Lock Nut 1
12	39857 N	Presser Spring Plunger Adjusting Screw
13	39857 C	Presser Spring, beavy, for all Styles except 39800 CA and CB1
-	39857 P	Presser Spring, light, for Styles 39800 CA and CB 1
14	51257 H	Lock Nut, for plunger adjusting screw 1
15	39857 E	Washer
16	39856 B	Presser Foot Release Lever
		resser foot kelease Lever 1
17	95	Screw, for oil system 1
18	39857 J	Presser Spring Plunger Stud 1
19	39857 M	Spacer1
20	CL21	Pipe Cleaner (oil wick)1
21	39857 A	Presser Spring Plunger Head1
22	22569 D	Screw, for thread tube
23	53634 C	Washer, for thread tube screw
24		washer, for thread tube screw 1
	39868 N	Thread Tube, for 401 looper thread 1
25	29477 MA	Upper Looper Thread Tube Assembly 1
26	22743	Screw, for thread tube tension spring
27	39568 J	Thread Tube Tension Spring
28	39568 P	Thread Tube
29	22548	Screw, for thread guide and mounting bracket
30	39892 B	Thread Guide, front 1
31		litead deide, front 1
32	39592 AH	Nut, for thread tension post 3 or 4
	39892 A-5	Tension Post Mounting Bracket 1
33	660-469	Retaining Ring, for tension post bar eyelet
34	39892 C	Tension Fost Bar Eyelet
35	39592 AN	Tension Fost Bar
36	8372 A	Washer, for thread tension post 3 or 4
37	39592 AL	
38	39592 AF	
39	39592 AD	
		Thread Tension Disc 6 or 8
40	39592 AR-2	Tension Spring, for 503 stitch needle on Styles 39800 CA, CP, CX, VCP and
		VCX
41	39592 AR-4	Tension Spring, for 503 stitch looper on Styles 39800 CA. CP. CX VCP and
-	39592 AR-4	Tension Spring, for 504 stitch needle on Styles 39800 CB, CQ, CY, VCQ and
_	39592 AR-4	VCI 1
	JyJy2 AR-4	Tension Spring, for 504 stitch looper on Styles 39800 CB, CQ, CY, VCQ and
42	20502 10 -	VCY
	39592 AR-5	Tension Spring, for 401 stitch needle 1
43	39592 AK	Tension Spring Ferrule 3 or 4
44	39592 Y	Upper Looper Tension Nut. black for Styles 39800 CB CO CV UCO and
		VCT
4 /	39592 Z	Lower Looper Tension Nut, golden beige1
-	39592 AA	Overedge Needle Tension Nut ereen
	39592 AC	Overedge Needle Tension Nut, green 1 401 Stitch Needle Tension Nut, red 1
45	22541 D	
	22341 D	Screw, for 401 stitch needle thread pull-off eyelet 1
46	22569 C	Screw, for overedge needle thread pull-off eyelet 1
47	8372 A	Washer, for Nos. 22541 D and 22596 C
48	22704	Screw, for 401 stitch needle thread pull-off eyelet 1
49	39863 K	401 Stitch Needle Thread Pull-off Evelet
50	39863 L	Overedge Needle Thread Pull-off Eyelet1
51	22565	
52	22585 R	
		Screy 1
53	39868 H	Figtail Eyelet, for 401 stitch looper thread 1
54	39868 Z	Thread Tube, for 503 or 504 stitch looper thread 1
55	22591	Screw, for oil stystem
56	HS24 C	Screw, for adjustable needle thread eyelet 2
57	39863 N	Adjustable Needle Thread Eyelet 1
58	22564 J	
59	39863 M	
-	3,003 11	Needle Thread Frame Eyelet 1




401 LOOPER TENSION PARTS, MISCELLANEOUS PLATES AND GUARDS

Ref.	Part No.	Description Reg.
		Description Req.
1	51292 C	401 Stitch Looper Tension Nut 1
2	51292 F-2	Tension Spring, for 401 looper 1
3	51292 G	Thread Tension Post1
4	109	Thread Tension Disc2
5	51292 A	Ferrule1
6	51292 D	Tension Thread Eyelet1
7	22571 E	Magnetic Oil Drain Plug 1
8	22569 K	Screw, for oil sight gauge 1
9	39893	Oil Sight Gauge 1
10	660-243	Oil Gauge Seal Ring1
11	39878 E	Chip Guard Assembly 1
12	39878 F	Chip Guard Base 1
13	43443 Q	Nut, for hinge pin2
14	660-210	Retaining Ring2
15	39158 U	Spring1
16	39878 C	Hinge Pin 1
17	39878 G	Chip Guard Cover1
18	22569 D	Screw, for chip guard 2
19	22585	Screw, for cast-off support plate 1
20	39868 B	Cast-off Support Plate 1
21	22585 C	Screw. for support plate end cover 2
22	39868 M	Support Plate End Cover 1
23	39835 D	Main Feed Bar Guide, left, for machines w/o
		"Air-Klipp" 1
24	39880 F	Throat Plate Support, rear, for machines w/o
		"Air-Klipp" 1
25	93 A	Screw, for rear throat plate support, for machines w/o
		"Air-Klipp" 1
26	39843 F	Plate Washer, for main feed bar guide screw 1
27	22541 B	Screw, for main feed bar guide 2
28	376 A	Screw, for finger protector1
29	25 S	Screw, for finger protector plate 2
30	21695 AB	Finger Protector Plate 1
31	39843 G	Washer 1
32	12934 A	Nut, for finger protector screw 1
33	21695 AA	Finger Protector1
34	21695 AM	Felt Pad1
35	22541 B	Screw, for cast-off support plate 2
36	8372 A	Washer, for cast-off support plate screw 2
37	73 A	Screw, for looper thread take-up eyelet 2
38	52958 D	Looper Thread Take-up Eyelet 2
39	39868 J	Cast-off Wire 1
40	77 A	Screw, for cast-off wire 2



PRESSER ARM AND FOOT LIFTER PARTS

Ref. No.	Part No.	Description	Amt. Req.
1	22797 A	Screw, for chain cutting knife and finger guard	1
2	53678 N	Washer	1
3	99682 M	Finger Guard, for all Styles except 39800 CX, CY, VCX, and VCY	
3A	21695 AL	Finger Guard, for Styles 39800 CX, CY, VCX and VCY	
4	22547 A	Screw, for chain cutting knife	1
5	39856 C	Chain Cutting Knife	
6	39656 B	Presser Arm, for No. 12 3/16 gauge, on Styles	- 1
		39800 CA and CB	- 1
_	39856 D	Presser Arm, for all Styles and gauges, except	
		No. 12 3/16 gauge, on Styles 39800 CA and CB	- 1
7	22791 H	Screw, for presser arm	
8	258 A	Nut, for presser arm screw	
9	39855 C	Foot Lifter Lever Shaft	
10	12865	Thrust Collar, for foot lifter lever shaft	
11	88	Screw, for thrust collar	
12	39857 H	Foot Lifter Lever Connecting Link	
13	660-142	Cotter Pin, for connecting link	
14	39855 A	Foot Lifter Lever Spring	
15	8372 A	Washer, for connecting link	
16	39555 C	Foot Lifter Lever Arm	
17	22597 E	Screw, for lever arm	
18	12538	Lock Nut, for lever arm screw	
19	627	Screw, for lever arm	
20	41332 J	Washer	
21	39855 B	Foot Lifter Intermediate Lever	
22	39855	Foot Lifter Lever	
23	22566 B	Screw, for foot lifter lever	
24	22571 D	Plug Screw, for foot lifter hole	
25		Presser Foot (See Pages 43 and 45)	




PRESSER FEET, FEED DOGS AND THROAT PLATES

			3980	O CA, CB	A SO	39800 CP, CQ		39800 VCP,VCQ
				Gauge		Gauge		
			5 1/8	12 3/16	5 1/8	8 3/16	12 3/16	12 3/16
Ref. Part No. No. PRESSER FOOT				er L	4			
3 39820 A-5 1/8			•		•	1 100	Twee!	IPA
26 39820 A-8 3/16					The same	•		Mild X
3 39820 A-12 3/16				•				•
DIFF. FEED DOG				1				10-1
	Teeth per in.	I.D. Mark		P.	73			
20 39626 D	16	"BR"	•		•	STATE	1	
21 39626 G	16	"BU"					Se.	
25 39826 B	16	"QG"		- 8			ST. ST.	
22 39826 A	. 12	"FT"				4		•
MAIN FEED DOG								
19 39805 G-5 1/8	16	"QC"	•				100	
17 39605 G-12 3/16	16	"DY-12"		•	1	1	Me.	
24 39805 A-8 3/16	16	"QE"				•		
15 39805 A-12 3/16	12	"FU"						
THROAT PLATE	I.D	. MARK					H	
18 39824 G-5 1/8	"DH-5	1/8"	•					
16 39828 J-12 3/16	"DL"			•			-	
23 39828 A-8 3/16	"DP-8	3/16"				•		
13 39824 A-12 3/16	"CN-1	2 3/16*						
14 39824 B-12 3/16	"CX"							

Ref.	Part	Description	I.D.	Amt.
No.	No.	Description		Req.
*1	39830 AJ	Shoulder Screw, for No. 39830 AL		1
*2	39830 AL	Spring for presser foot bottom		1
4 5	22733	Set Screw, for presser foot bottom hinge pin	"M"	
5	39830 39830 G	Presser Foot Shank, for No. 12 3/16 gauge	"N"	1
-	22588 A	Presser Foot Shank, for No. 5 1/8 gauge Clamp Screw		1
6 7	39830 A	Needle Hole Section, for No. 12 3/16 gauge	"BC"	î
	39830 H	Needle Hole Section, for No. 5 1/8 gauge	"BD"	1
9	39830 S	Spring, for needle hole section	-	1
8	39830 F	Hinge Screw, for needle hole section		1
10	39830 B	Locknut Screw, for No. 12 3/16 gauge needle hole section		1
	39830 J	Locknut Screw, for No. 5 1/8 gauge needle hole section		1
11	39830 E	Hinge Pin, for presser foot bottom		1
12	39830 C	Presser Foot Bottom, for No. 12 3/16 gauge	"BZ-12 3/16"	1
	39830 K	Presser Foot Bottom, for No. 5 1/8 gauge	"cc"	1
39820	A-8 3/16			
27	22799 AF	Hinge Screw, for presser foot bottom		1
28	39830 F	Hinge Screw, for needle hole section		1
29	39830 AB	Spring, for needle hole section		1
30	39830 Y	Needle Hole Section	"BG"	1
31	39830 J	Locknut Screw	***	1
32	39830 T	Presser Foot Shank	-R-	1
33	22588 A	Clamp Screw	"CF"	+
34	39830 W	Presser Foot Bottom	CF.	-

*Not components of presser foot assembly



PRESSER FEET, FEED DOGS AND THROAT PLATES


	9//2			39800	CX, CY	39800 VCX,VCY
				G	auge	Gauge
				8 3/16	12 3/16	12 3/16
Ref. No.	Part No. PRESSER FOOT	1 15		200		
5	39820 E-8 3/16				2 11	
20	39820 E-12 3/16	- ded		Mars	•	
	DIPF. FEED DOO	Teeth per in.	I.D. Mark	308		
3	39826 B	16	"QG"	•		1000
19	39826 A	12	"FT"		•	•
	MAIN FEED DOG	1			M-K	100
2	39805 E-8 3/16	16	"QF"			20
18	39805 E-12 3/16	16	"PY"			•
	THROAT PLATE			1 50 W	1911	1
4	39828 E-8 3/16		"DR"		24	
16	39828 E-12 3/16		"EE"		•	-
17	39828 F-12 3/16	1 1	"ED"	74		

PRESSER FEET - Component Parts

820		


Ref. No.	Part No.	Description	I.D. Mark	Amt. Req
*1	39830 AJ	Shoulder Screw, for tractor foot		1
6	22799 AF	Hinge Screw, for presser foot bottom		1
6	39830 X	Needle Hole Section	"BF"	1
8	22733	Set Screw		1
9	39830 AH	Tractor Foot Spring		1
10	39830 U	Presser Foot Shank	"S"	1
11	22588 A	Clamp Screw		1
12	39830 AT	Hinge Pin		1
13	39830 Z	Presser Foot Yoke		1
14	39830 AA	Hinge Screw		1
15	39830 V	Presser Foot Bottom	"CE"	1
39820	E-12 3/16			
*1	39830 AJ	Shoulder Screw, for tractor foot		1
21	39830 AT	Hinge Pin		2
22	39830 N	Needle Hole Section	"BE"	1
23	39830 AH	Tractor Poot Spring		1
24	22733	Set Screw		3
25	39830 M	Presser Foot Shank	"P"	1
26	22588 A	Clamp Screw		1
27	39830 R	Presser Foot Yoke		1
28	39830 AK	Hinge Pin		1
29	39830 P	Presser Foot Bottom	"CD"	1

^{*} Not a component of presser foot assembly



"AIR-KLIPPW CHAIN CUTTER AND PNEUMATIC PARTS (For Styles 39800 VCP, VCQ, VCX, VCY)

Ref. Part Amt. No. Description Req. 1 22562 A Screw
1 22562 A Screw 2 2 77 Screw 2 2 77 Screw 2 2 3 39880 K Throat Plate Support, rear 1 4 39880 G Throat Plate Support Bracket, rear 1 5 629911 Q Air-Klipp Assembly 1 6 22829 Screw 2 2 22519 Screw 2 2 2 2 2 2 2 2 2
2 3 39880 K
3 39880 K Throat Plate Support, rear 1 4 39880 G Throat Plate Support Bracket, rear 1 5 629911 Q Air-Klipp Assembly
4 39880 G Throat Plate Support Bracket, rear 5 629911 Q Air-Klipp Assembly
Second Color Color
6 22829 Screw 2 2 7 22519 Screw 2 8 53634 C Hasher 1 9 99669 A Movable Knife 1 10 95910 Hasher 1 11 99667 B Knife Lever 1 13 99674 B Screw 1 13 99674 B Stud 1 14 59663 F Base - 1 15 13430 L 011 Wick - 1 16 22894 W Set Screw - 1 17 622894 W Set Screw - 1 18 99672 Knife Driving Link - 1 19 99673 Link Bushing - 1 19 99673 Link Bushing - 1 20 99671 Stud, for link - 1 21 22716 A Screw - 2 299677 B Inlet Part, marked "GC", for No. 8 3/16 and 12 3/16 gauge machines 1 1 Inlet Part, marked "GC", for No. 5 1/8 gauge machines 1 23 99676 K Air-Kilpp Tube, complete 1 24 99670 C Upper Knife 1 25 22716 Screw 2 26 671 B-12 Air Tube, 12 Inches (304.80 mm) long 1 2 Screw 2 2
7 22519 Screw 1 8 53634 C Hasher 1 9 99669 A Movable Knife
8 53634 C
9 99669 A Movable Knife
10 95910
11 99667 B
12 2284 W Set Screw 1 13 99674 B Stud
13 99674 B Stud
14 99663 F Bane
15
16 22894 W Set Screw 1 1 17 17 18 19 19 18 19 19 19 19
17 G22797 A Screw 1 18 99672 Knife Driving Link 19 99673 Link Bushing 20 99671 Stud, for link
18 99672 Knife Driving Link
19 99673 Link Bushing - 1 20 99671 Stud, for link - 1 21 22716 A Screw - 2 22 99677 B Inlet Part, marked "CC", for No. 8 3/16 and 12 3/16 gauge machines - 1 - 99677 F Inlet Part, marked "CC", for No. 5 1/8 gauge machines - 1 23 99676 K Air-Klipp Tube, complete - 1 24 99670 C Upper Knife - 1 25 22716 Screw - 2 26 671 B-12 Air Tube, 12 Inches (304.80 mm) long - 1 27 22541 B Screw - 2
20 99671 Stud, for link 1 21 22716 A Screw 2 22 99677 B Inlet Part, marked "CC", for No. 8 3/16 and 12 3/16 gauge machines 1 - 99677 F Inlet Part, marked "GC" for No. 5 1/8 gauge machines - 1 23 99676 K Air-Kilpp Tube, complete - 1 24 99670 C Upper Knife - 1 25 22716 Screw 2 26 671 B-12 Air Tube, 12 inches (304.80 mm) long - 1 27 22541 B Screw 2
22716 A Screw 2 2 2 99677 B Inlet Part, marked "CC", for No. 8 3/16 and 12 3/16 gauge machines 1 2 3/16 gauge machines 1 1 1 1 1 1 1 1 1
22 99677 B Inlet Part, marked "CC", for No. 8 3/16 and 12 3/16 gauge machines 1 11st Part, marked "GC", for No. 5 1/8 gauge 12 99677 F Inlet Part, marked "GC", for No. 5 1/8 gauge 12 99676 K Air-Kilpp Tube, complete 1 12 99670 C Upper Knife - 1 12 22716 Screw - 2 12 22716 Screw - 2 13 Screw - 2 14 Screw - 2 15 22541 B Screw - 2
12 3/16 gauge machines 1 1 1 1 1 1 1 1 1
- 99677 F Inlet Part, marked "CG", for No. 5 1/8 gauge machines - 1 23 99676 K Air-Klipp Tube, complete - 1 24 99670 C Upper Knife - 1 25 22716 Screw - 2 26 671 B-12 Air Tube, 12 inches (304.80 mm) long - 1 27 22541 B Screw - 2
machines 1
23 99676 K Air-Klipp Tube, complete 1 24 99670 C Upper Knife 1 25 22716 Screw 2 26 671 B-12 Air Tube, 12 Inches (304, 80 mm) long 1 27 22541 B Screw 2
24 99670 C Upper Knife
25 22716 Screw 2 26 671 B-12 Air Tube, 12 inches (304.80 mm) long
26 671 B-12 Air Tube, 12 inches (304.80 mm) long1 27 22541 B Screw
27 22541 B Screw 2
20 37043 r washer riate
29 671 D-2 Air Jet 1
30 671 B-3 Air Tube, 45 inches (1143.0 mm) long 1
31 39583 A Mounting Bracket 1
32 671 D-7 Pressure Regulator And Gauge 1
33 671 F-8 Straight Fitting1
34 671 F-6 Reducer Bushing 1
35 671 F-1 Male Fitting 2
36 671 B-1 Air Tube, 36 inches (914.40 mm) long 1
37 61242 Pitman Rod Collar 1
38 88 Screw 2
39 671-2 Air Valve Mounting Block 1
40 22651 CB-4 Set Screw 2
41 671-3 Air Valve Actuator Block 1
42 1453 A Pitman Rod 1
43 21371 MZ Connection1
44 671-1 Air Valve 1
45 22729 B Screw 2
46 671 F-2 Elbow Fitting 1
47 671 B-11 Air Tube, 30 inches (762.0 mm) long 1
670 E-2 Cable Tie (not shown) 3



THREAD STAND AND ACCESSORIES

Ref.	Part		Amt.
No.	No.	Description	Req.
			med.
1	21101 H-4	Thread Stand, complete, for 4 cones, for Styles	
		39800 CA, CP, CX, VCP and VCX	1
+ 1A		Thread Stand, complete, for 6 cones, for Styles	
22.0		39800 CB, CQ, CY, VCQ and VCY	1
2	21114 S-4	Lead Eyelet, for No. 21101 H-4	1
-	21114 AL-5	Lead Eyelet, for 5 threads	1
3	258 A	Nut	8 or 10
4	652-16	Washer	4 or 5
5	21114	Spool Seat Disc	4 or 5
6	21114 W	Spool Pin	4 or 5
7	21104 V	Pad, for thread cones	4 or 5
8	21114 H-4	Eyelet Support, for No. 21101 H-4	1
-	21114 H-6	Eyelet Support, for 6 threads	1
9	22651 CD-4	Screw	1
10	21104 B-24	Thread Stand Rod	1
11	21114 D-4	Spool Seat Support, for No. 21101 H-4	1
-	21114 D-6	Spool Seat Support, for 6 threads	1
12	22651 CD-5	Screw	2
13	21104 H	Nut	1
14	652-16	Washer	1
15	21114 U	Lead Eyelet Ball Split Socket	2
16	21114 A	Thread Stand Base	1
17	22651 CD-4	Screw	1
18	22810	Clamp Screw	1
19	21114 T	Lead Eyelet Socket Ball	1
20	22651 CD-4	Screw	2
21	421 D-34	Foot Lifter Treadle Chain, 34 inches (863,60 mm)	-
		long	1
22	21388 AU	Socket Wrench, for 3/8 inch (9.52 mm) hexagonal	
		nut holding feed eccentric	1
23	21388 W	Wrench, curved double end, 9/32 inch (7.14 mm)	
		opening	1
24	21227 BF	Feed Eccentric Extractor Hook	1
*25	21225-3/32	Looper Gauge, 3/32 inch (2.38 mm)	1
26	660-272	Thread Tweezers	1
27	21207 B	Screwdriver, 1/8 inch (3.18 mm) diameter	1
28	660-264	"S" Hook for treadle chain	2
29	WR56	Wrench, 1/8 inch (3.18 mm) hexagonal	1
30	WR65	Wrench, 1/16 inch (1.59 mm) hexagonal	1
31	WR69	Wrench, 9/64 inch (3.58 mm) hexagonal	1
-	660-458	Dust Cover (not shown)	1
-	39899 A	Threading Wire (not shown)	1
-	SC-303	Wood Screw, #12 x 1 inch (25.4 mm) long (not shown)	3
-	28604 R	Container of Oil, 16 ounces, Spec. 175 (not shown)	1
-	652-24	Washer, for use in tableboard (not shown)	8
*	39803	Edge Guide, cloth plate mounted (not shown)	1
*	29481 J	Edge Guide (not shown)	1
sk	21227 DD	Needle Height Gauge (not shown)	1
*	21394 N	Knife Grinder (not shown)	1
*	39598 G	Swinging Frame - required with No. 21394 N	
		(not shown)	1

^{*} Available as extra send and charge item.

⁺ Number for complete thread stand not available, order component parts.

				X O		

Page No. Part No. Page No.

Part No.

Page No.

Part

1.00		36	No.	No. No.	30.		2624
Color	_	CONTRACTOR OF THE PARTY OF THE					
Color		20-1	.29.35	15430 L	227	69 3	.27
OCO T. 27		CT 21	20 27	21101 W-4 40	227	75	-33
OCO T. 27		Chile	.63,31		227	22	22
OCO T. 27		22 KH	.35	Z1104 B-Z4	241	01	.33
OCO T. 27		ES24 C	,37	21104 E	227	84 L	.29
OCO T. 27			30	21104 V	227	91 H	-41
OCO T. 27		22 2	24	22224 46	222	07 5	4.1
OCO T. 27		28 C	.29	21114		31 A	147
OCO T. 27		30-106 Blk	.27	21114 A	0227	97 A	.47
OCO T. 27		40-130	.79	21114 B-4	227	99 AF	.43.45
OCO T. 27		62 226 PAR	92	21116 8-6 68	220	04 4	25
OCO T. 27		31-230 BIR	127	21114 0-0	220	00 4	10
OCO T. 27		WR56	.49	21114 8-4 49	228	10	.49
2007 1. 27 27 2114 6. 69 22891 3. 3.		WR65	.49	21114 H-6		24 8	.25
77 A		CO67 F	.27	21114 5-4	228	29	.47
77 A		0007 8	10	2111/ 6 /0	110	62 6	20
88 F		MX09	.49	21114 1			
88 F		73 A	.39	21114 U	228	92 8	.35
88 F		77	.27.31.47	21114 W	228	94 C	.29.31.33.
88 F		77 4	50	21117 11-5 /0			35
88 F		// A	.37	21114 20-3	220		0.0
88 F		87 U	.29,35	21207 3	228	94 D	+21
660-102.			.25,41,47	21225-3/32	228	94 J	.27,31,35
660-102.		68 T	15	21227 RF	278	94 L	-29.35
660-102.		00 1		21227 20 /0	220	AT W	97
660-102.		90	.23,33	21227 00	220	24 0	+6.4
660-102.		93	.27	21371 1/2	228	94 8	.47
660-102.		93 A	.27.39	21388 W	228	95 AE	.31.33
660-102.			42 42	31 369 AH /A	226	61 19	33
660-102.		93	.21,31	21300 MV	220	A. W	
660-102.			.35	21394 5	228	79 AG	+63
660-102.		97 A	.27	21695 AA	286	04 E	.49
660-102.		40	13	21695 48 39	36/	77 MA	-37
660-102.		70	. 33	2007	234	22 20	22
660-102.		109	.39	21090 AL	294		161
660-102.		120 G5	.29	21695 AM	294	77 107	.27
660-102.		120 C18	20	22503 F	261	81 J	.42
660-102.		140 000	-		234		4.9
660-102.		135	.23	22319 47	C259	11 Q	-4/
660-102.		258	.27	22524	391	51	.31
660-102.		258 4	41.40	22541 N	47 391	58 U	.39
660-102.			10	20111 2	371	(A) V	95
660-102.		SC303	.07	22341 0	393	M. A	103
660-102.		376 A	.37.39	22547 A	395	01 08	.25
660-102.		421 D-74	.49	22548	395	O1 DU	.25
660-102.		180 0	21 22 15	22562 4 32 35	47 395	16-625	.27
660-102.		402 0	131,331,33	20000 20	204	16 626	22
660-102.		538	.31,33	22304 9	393	710-020	161
660-102.		605	.29	22564 G	393	/16-52/	16/
660-102.		627	.41	22564 J	395	21 G	.27
660-102.		669.16	10	22565 37	191	484	.27
660-102.		032-10	10	20166 0 22	205	24.0	27
660-102.		05Z-Z4	197	22,70,7 0	373	24 0	107
660-2209 -9 -2200 h27,37 -2505 f27,38 -660-2209 -9 -2200 h27,37 -2505 f27,37 -27,37		660-142	.61	22300 %	393	/33 3	121
660-2209 -9 -2200 h27,37 -2505 f27,38 -660-2209 -9 -2200 h27,37 -2505 f27,37 -27,37		660-206	.31.33.35	22566 3 41	395	36 B	.27
600-441,		(40.310	30	22560 25	395	36 C	. 27
600-441,		000-210		22776 2 22 22	101	24. E	97.99
600-441,		560-220	.29	22307 3	373	20 5	+41,00
600-441,		660-243	.39	22569 C	393	36 AE	.27
600-441,		660-264	.49	22569 0	.39 395	36 AF	.27
600-441,		640-268	27	22569 C	195	60 B-8	.27
600-441,		000-200	10.	22770 7	101	10 m-10	93
600-441,		660-272	.49	22307 %	393	WO E-10	+6.7
669-469. 47 22285 L. 35 39543 E. 37.3,35 66-435. 37 39543 E. 37.3,35 2226 E. 37 39543 E. 3		660-416	.29	225/1 0 41	393	MI do	+21
669-469. 47 22285 L. 35 39543 E. 37.3,35 66-435. 37 39543 E. 37.3,35 2226 E. 37 39543 E. 3		660-442	.29	22571 E	395	43	.35
669-469. 47 22285 L. 35 39543 E. 37.3,35 66-435. 37 39543 E. 37.3,35 2226 E. 37 39543 E. 3		660-113	27	22572 8	195	43 A	-35
669-469. 47 22285 L. 35 39543 E. 37.3,35 66-435. 37 39543 E. 37.3,35 2226 E. 37 39543 E. 3		000-043	141	20000		42.8	22 25
660-206. 35 22355 C. 99 3954 F. 33,33 5 6 6 6 6 355 C. 39 3954 F. 33,35 5 6 6 6 6 6 3 6 6 6 6 6 6 6 6 6 6 6 6		660-438	.49	22389	393	M3 2	.33,33
100 A		660-669	.37	22585 A	395	43 M	.33,35
100 A		660=506	.25	22585 C	395	43 F	.33.35
100 A			22 22	20000 0 27	101	43 €	25
100 A		000-233	131,33	22203 8	392		***
100 A		665-268	.25	22586 R 25	395	143 T	.33
100 A		666-221	25	22587 F	395	43 W	.35
100 A			30	23597 W 27	305	414.9	31
100 A		000-280	163	22/01 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	393		21
100 A		665-290	.23	ZZ385 A	.43 395	pag 20	+31
100 A		670 E=2	.47	22588 J	395	544 J	.35
100 A		671-1	47	22591	391	144 L	.25
100 A		Mrs-1	17	22/07 9	39.1	150 0	25
100 A		6/1-2	.9/	22397 5	393	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	.03
100 A		671-3	.47	22650 AE-4 25	395	150 E	.35
100 A		671 H-1	-47	22651 CB-4	395	550 M	.35
100 A		671 1-9	62	22651 57-4 46	201	550 Z	.35
100 A		0/1 5-3		20/51 00 5	371	455.0	41
100 A		671 B-11	.47	22001 00-0	395		147
100 A		671 8-12	.47	22652 A-6	395		
100 A		671 D=2	.47	22652 3-10	391	568 E	.37
100 A		431 0 3	43	22452 3-12 35	291	W. T	-37
100 A		0/1 0-/	12	22/42 2 4	37.	449 1	37
100 A		0/1 F-1	*41	22903 3-4,	393		- 3/
100 A		671 F-2	.47	22657 0-12	393	Me T	-37
100 A		671 F-6	.47	22704	395	571 8	.33
100 A		671 7-8	47	22716	391	571 C	.33
100 A		1021	24	22716 4	201	579 A.	.33
100 A		1023	.33	22/10 A	393		20 22
			.47	22729 5 35,47	395	373 A	.29,33
		6042 A	.33	22729 D	35 395	573 E	.33
		9322 A	25 37 30	19229 F	391	573 K	.25
			107011271	22700 W 23	201	672 44	25
				22/27 %	16 39.	27.5 cm	24
		9937		22733	.40 395	210 8	163
		12538	.41	22738	393	380 F	.35
		12965	-41	22718 8	39	582 F	.25
1-273 th		10001	4.0	227/2		182 39	25
12982		14934 4		227731	39.	CO2 27	26
14077		12982	.31,33	22/4/ 8	393	302 85	143
		14077	.35	22768 E	395	18Z 18f	+45

			DE		

Part

Part Page

Part

No. No.	No.	No.	No.	No.
39582 BV 25	39828 E-12 3/16	45	39860	35
39583 A	39828 F-12 3/16	45	39863	29
39590	39828 J-12 3/16	43	39863 C	29
39590 C	39830	43	39863 D	. 29
39590 G	39830 A	43	39863 D	79
39590 7 27	39830 B	. 43	39863 K	. 37
39590 R	39830 C	43	39863 L	37
39590 S	39830 E	43	39863 M	37
39590 R	39830 C	43	39863 L	37
39591 Н	39830 G	43	39868 B	39
39591 H	39830 G	43	39868 B	37
39591 L	39830 J	43	39868 н	37
39592 Y	39830 K	43	39868 M	39
39592 Z	39830 M	45	39868 м	39
39592 AA 37	39830 N	45	39868 N	37
39592 AC	39830 P	45	39868 R	27
39592 AD	39830 K	43	39868 X	37
39592 AG	39830 R	43	39868 X. 39868 X. 39868 Z. 39870. 39871. 39873.	3/
39392 AB	30030 1	43	39000 2	3/
39592 AK	39830 U	43	39870	33
39392 AL	39630 V	43	20072	33
39592 AD-7 37			30873 3	33
39592 AR-4	39830 Y	43	39878 C	39
37932 AA	39830 Y 39830 Y 39830 Z 39830 AA 39830 AB 39830 AB 39830 AJ	45	39873 3. 39878 G. 39878 E. 39878 F. 39878 F. 39878 G. 39878 G. 39880 G. 39880 F. 398	39
39593 C 25	39830 AA	45	39878 7	39
39593 D 25	39830 AB	43	39878 G	39
39593 J	39830 AH	45	39880	35
39593 K	39830 AJ	43,45	39880 F	39
39593 L 25	39830 AK	45	39880 G	47
39594 N	39830 AL	43	39880 H	35
39595	39830 AL	45	39880 K	47
39598 G	39832	25	39882	25
39605 G-12 3/16	39834 B	25	39882 E	25
39593 L	39835 A	27	3980 G. 3980 H. 39880 K. 39882 E. 39882 F.	25
39626 D	39835 B	27	39882 G	25
39626 G	39835 C	27	39882 J	25
39044	39838	39	39883	33
39644 C 35	39030	25	39890 €	2/
39625 B	39843 A	35	39882 F. 39882 G. 39882 J. 39883. 39890 C. 39890 E. 39892 A-5.	27
39644 K		35	39892 A-3	37
39646 L	39843 C	- 35	39892 C	37
39644 L	39843 C	29	39892 C	. 39
39644 N	39843 E	35	39893 C	25
39644 P	39843 F	39,47	39894 A	25
39644 P	39843 F	39	39894 A	25
39644 R-5	39843 H	35	39894 C	31
37644 V	39844 A	31		
39644 U	39844 A	33	41071 G	35
39644 V	39844 B	31	41332 J	41
39644 W	39844 C	33	41336 C	33
39644 X	39844 D	33	43443 Q	39
39650	39849	35	51236 A	29
39630 A	39832	29	51257 H	37
39656 B	39852 A	20	51292 A	39
39673	10052 0	20	51292 C	39
	39852 F	. 29	51292 F-2	20
39803	39852 D 39852 F-5 39852 F-8 39852 F-8 39852 F-12 39852 J 39852 K-5 39852 K-5 39852 K-5 39852 K-8 39852 M	29	31237 H. 31292 C. 31292 C. 31292 D. 51292 P. 51292 F. 51292 C. 51295 B. 52344. 52958 D. 53678 R. 53678 R.	. 39
39803	39852 F-8	29	51295 B	25
39805 A-12 3/16	39852 F-12	29	52344	31
39805 E-8 3/16 45	39852 J	29	52958 D	39
39805 A-12 3/16	39852 K-5	29	53634 C	37.47
39805 C-5 1/8	39852 K-8	29	53678 N	41
39808	39852 K-12	29	55235 D	33
39808 A	39852 M	25	55235 E	33
39808 C			56393 G	25
39808 D	39855 A	41	56393 V	25
39820 A-5 1/8	39855 A	41	61242	47
39820 A-8 3/16	39855 8	41	95910	47
39820 A-12 3/16	39855 C	41	530/8 %	. 47
37020 5-0 3/10 43	39033 0	23	9900/ 8	. 47
39820 E-12 3/16	39030 D	3/	99667 B	4/
39824 A-12 3/16 42	39856 D	41	99671	1.7
39824 A-12 3/16 43 39824 B-12 3/16	10857 A	37	99672	17
39824 G-5 1/8				
	19857 E	37	99674 R.	47
39825 B	39857 E	41	99674 B	47
39825 C	39857 J	37	99677 K	47
39826 A			99677 F	. 47
39826 B	39857 M	37	99677 F	41
39826 A	39857 N	37		
39828 E-8 3/16 45	39857 P	37		